

# DETERMINATION OF STRESS STRAIN CURVES OF 304, 304L, 316, 316L FOR STRAIN-BASED DESIGN CRITERIA



STP-PT-094

# DETERMINATION OF STRESS STRAIN CURVES OF 304, 304L, 316, 316L FOR STRAIN-BASED DESIGN CRITERIA

*Prepared by:*

Wolfgang Hoffelner  
RWH consult GmbH



Date of Issuance: February 28, 2022

This publication was prepared by ASME Standards Technology, LLC (“ASME ST-LLC”) and sponsored by The American Society of Mechanical Engineers (“ASME”).

Neither ASME, ASME ST-LLC, the author, nor others involved in the preparation or review of this publication, nor any of their respective employees, members, or persons acting on their behalf, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe upon privately owned rights.

Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by ASME ST-LLC or others involved in the preparation or review of this publication, or any agency thereof. The views and opinions of the authors, contributors and reviewers of the publication expressed herein do not necessarily reflect those of ASME ST-LLC or others involved in the preparation or review of this publication, or any agency thereof.

ASME ST-LLC does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a publication against liability for infringement of any applicable Letters Patent, nor assumes any such liability. Users of a publication are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representative(s) or person(s) affiliated with industry is not to be interpreted as government or industry endorsement of this publication.

ASME is the registered trademark of The American Society of Mechanical Engineers.

No part of this document may be reproduced in any form,  
in an electronic retrieval system or otherwise,  
without the prior written permission of the publisher.

ASME Standards Technology, LLC  
Two Park Avenue, New York, NY 10016-5990

ISBN No. 978-0-7918-7512-4  
Copyright © 2022  
ASME Standards Technology, LLC  
All Rights Reserved

## TABLE OF CONTENTS

Abstract .....	iii
1 Introduction .....	1
2 Choice of Stress-Strain Curve .....	2
3 Determination of Strain at Ultimate Tensile Stress .....	4
4 Ultimate Tensile Stress and Rupture Strain.....	5
5 Maximum and Minimum YS/UTS.....	6
6 Maximum/Minimum True Stress/Strain at Fracture .....	9
7 Temperature Dependence of Yield stress and Ultimate Tensile Stress.....	11
8 True Fracture Strain.....	12
9 Low-Temperature Stress-Strain Curves .....	13
10 Strain-Rate Dependence .....	16
11 Final Curves: Some Examples.....	18
References.....	22
Appendix A: Short- and Long-Term Goals for the Task Group on Materials Supporting Division 3 Strain-Based Criteria .....	33
A.1 Short-Term Goals .....	34
A.2 Long-Term Goals.....	35

### LIST OF TABLES

Table 5-1: Relationships between UTS, YS and Hardness.....	8
Table 9-1: Temperatures when 50% Martensite is Formed after 30% Strain (Md(30/50) C) .....	15
Table 10-1: Strain-Rate Adjustment Factors .....	17
Table A-1: Permitted Material Specifications and Products.....	34

### LIST OF FIGURES

Figure 2-1: Comparison of Measured Strain at Ultimate Tensile Stress of Experimental Values (INL) [1] with calculated values (m2 in Section VIII, Division 2) .....	2
Figure 2-2: Comparison of Calculated Stress-Strain Curves with Measured Curves .....	3
Figure 3-1: Engineering Fracture Strain as a Function of Engineering Strain at UTS Using Different Data Sources where Strain at UTS and Engineering Fracture Strain were available.....	4
Figure 3-2: Relationship between engineering strain at ultimate tensile stress (UTstrain) and engineering fracture strain (EFS). Data replotted from Figure 3-1.....	4
Figure 4-1: Dependence of Fracture Elongation on UTS: No significant correlation exists .....	5
Figure 5-1: Relation between YS and UTS for Austenitic Steel at Room Temperature.....	6
Figure 5-2: Influence of a 20% Yield Stress Difference on Stress-Strain Curve for Same UTS Values	7
Figure 6-1: Extreme Possibilities to Obtain True Stress-Strain Curves between UTS and Final Fracture .....	9
Figure 6-2: Tangent Moduli for Different 304 and 316 Tests (metric units) at Various Temperatures; Scatterband Upper Bound 700, Lower Bound 400 .....	10
Figure 7-1: Yield Stress and Ultimate Tensile Stress for Several 304-Type and 316L Type Data .....	11
Figure 7-2: Comparison of INL Data with YS and U-Table Values .....	11
Figure 8-1: True Fracture Strain of 304L and 316L .....	12
Figure 9-1: Typical Stress-Strain Curves for 304L (Engineering) and 316L (True) at -20F (INL data)	13

Figure 9-2: True Stress-Strain Curves for 304L Measured at -20°F up to UTS compared to Proposed Minimum and Maximum Stress-Strain Curves..... 13

Figure 9-3: Formation of Martensite in Austenites..... 14

Figure 10-1: Yield Stress Ratio as a Function of Strain Rate ..... 16

Figure 11-1: Upper and Lower Bound Stress-Strain Curves for 304L at Room Temperature ..... 18

Figure 11-2: Comparison of true stress-strain curve determined with Ramberg-Osgood-type of evaluation (blue line) with parametric approach (green line). Material 304L measured at room temperature ..... 19

Figure 11-3: Parameter a as function of temperature (a low represents the lower bound curve and a high refers to the upper bound curve) ..... 19

Figure 11-4: Parameter b as function of temperature (b low represents the lower bound curve and b high refers to the upper bound curve) ..... 20

Figure 11-5: Parameter c as function of temperature (c low represents the lower bound curve and c high refers to the upper bound curve) ..... 20

Figure 11-6: Parameter d as function of temperature (c low represents the lower bound curve and c high refers to the upper bound curve) ..... 21

Figure 11-7: Parameter e as function of temperature (c low represents the lower bound curve and c high refers to the upper bound curve) ..... 21