

ASME B5.60-2014
(Revision of ASME B5.60-2002)

Workholding Chucks: Jaw-Type Chucks

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**

ASME B5.60-2014
(Revision of ASME B5.60-2002)

Workholding Chucks: Jaw-Type Chucks

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**

Two Park Avenue • New York, NY • 10016 USA

Date of Issuance: February 6, 2015

This Standard will be revised when the Society approves the issuance of a new edition.

ASME issues written replies to inquiries concerning interpretations of technical aspects of this Standard. Interpretations are published on the Committee Web page and under go.asme.org/InterpsDatabase. Periodically certain actions of the ASME B5 Committee may be published as Cases. Cases are published on the ASME Web site under the B5 Committee Page at go.asme.org/B5committee as they are issued.

Errata to codes and standards may be posted on the ASME Web site under the Committee Pages to provide corrections to incorrectly published items, or to correct typographical or grammatical errors in codes and standards. Such errata shall be used on the date posted.

The B5 Committee Page can be found at go.asme.org/B5committee. There is an option available to automatically receive an e-mail notification when errata are posted to a particular code or standard. This option can be found on the appropriate Committee Page after selecting “Errata” in the “Publication Information” section.

ASME is the registered trademark of The American Society of Mechanical Engineers.

This code or standard was developed under procedures accredited as meeting the criteria for American National Standards. The Standards Committee that approved the code or standard was balanced to assure that individuals from competent and concerned interests have had an opportunity to participate. The proposed code or standard was made available for public review and comment that provides an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not “approve,” “rate,” or “endorse” any item, construction, proprietary device, or activity.

ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable letters patent, nor assumes any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representative(s) or person(s) affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations of this document issued in accordance with the established ASME procedures and policies, which precludes the issuance of interpretations by individuals.

No part of this document may be reproduced in any form,
in an electronic retrieval system or otherwise,
without the prior written permission of the publisher.

The American Society of Mechanical Engineers
Two Park Avenue, New York, NY 10016-5990

Copyright © 2015 by
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS
All rights reserved
Printed in U.S.A.

CONTENTS

Foreword	v
Committee Roster	vi
Correspondence With the B5 Committee	vii
1 General Description and Definitions of Terms	1
2 Chuck-to-Spindle Interface	4
3 Jaw Mountings	37
4 Performance Testing	69
5 Safety Code of Practice	74
Figures	
1-1 Example of a Power Chuck Assembly	2
1-2 Exploded View of a Typical Manual Chuck	3
1-3 Exploded View of a Power Chuck	3
2-1 Type A Spindle Location of Holes and Drive Button for Sizes A-5 Through A-11	6
2-2 Type A Spindle Location of Holes and Drive Button for Sizes A-15 Through A-28	7
2-3 Type A Spindle Dimensions for Sizes A-3 Through A-28, and Location of Holes and Drive Button for Sizes A2-3 and A2-4	8
2-4 Type C Spindle	10
2-5 Type C Spindle Location of Holes	11
2-6 Type D Spindle	13
2-7 Type A Spindle	14
2-8 Type D Spindle Location of Holes for Size D-3	15
2-9 Type D Spindle Location of Holes for Size D-4	16
2-10 Type D Spindle Location of Holes for Sizes D-5 Through D-20	17
2-11 Type D Spindle Cam for Size D-3	18
2-12 Type D Spindle Cam for Size D-4	19
2-13 Type D Spindle Cams for Sizes D-5 Through D-20	20
2-14 Type D Spindle Detent and Cam Screws	21
2-15 Type D Spindle Detent and Cam Springs	21
2-16 Type D Spindle Detent Plunger	21
2-17 Type A Chucks and Faceplates	25
2-18 Type A Chuck and Faceplate Dimensions	26
2-19 Type C Chucks and Faceplates	28
2-20 Type C Chuck and Faceplate Dimensions	29
2-21 Type D Chucks and Faceplates	31
2-22 Types D-3 and D-4 Backs of Chucks and Faceplates	32
2-23 Types D-5 Through D-20 Backs of Chucks and Faceplates	33
2-24 Type D Cam Lock Studs and Stud Locking Screw	34
3-1 Fastener Guidelines	38
3-2 Jaw Interface Flatness Guidelines	39
4-1 Spindle Verification Test for Chuck Mounted Directly on the Test Spindle	69
4-2 Spindle Verification Test for Chuck Mounted on an Adapter	70
4-3 Geometric Tests	70
4-4 Manual-Scroll Chucks: Checking Centering Accuracy and Repeatability of Outside-Diameter Grip	71
4-5 Manual-Scroll Chucks: Checking Centering Accuracy and Repeatability of Jaw Steps	72

4-6	Power Chucks: Checking Centering Accuracy and Repeatability for External Chucking	72
4-7	Power Chucks: Checking Centering Accuracy and Repeatability for Internal Chucking	73

Forms

5-1	Sample Maintenance Schedule Sheet	77
5-2	Sample Grip Force Log Sheet	78

Tables

2-1	Type A Spindle Dimensions	9
2-2	Type C Spindle Dimensions	12
2-3	Type D Spindle Dimensions	22
2-4	Type D Spindle Cam Dimensions	23
2-5	Type D Spindle Detent and Cam Screws Dimensions	24
2-6	Type D Spindle Detent and Cam Spring Dimensions	24
2-7	Type D Spindle Detent Plunger Dimensions	24
2-8	Type A Chuck and Faceplate Dimensions	27
2-9	Type C Chuck and Faceplate Dimensions	30
2-10	Type D Chuck and Faceplate Dimensions	35
2-11	Type D Chuck and Faceplate Stud Dimensions	36
2-12	Type D Chuck and Faceplate Stud Locking Screw Dimensions	36
3-1	Top-Jaw Features	40
3-2	Tongue and Groove, Medium Duty Chucks, Wrench Operated	42
3-3	Tongue and Groove, Medium Duty Chucks, Three-Step Reversible Top Jaw, Wrench Operated	44
3-4	Tongue and Groove, Heavy Duty Chucks, Wrench Operated	45
3-5	Tongue and Groove, Heavy Duty Chucks, Three-Step Reversible Top Jaw, Wrench Operated	47
3-6	Tongue and Groove, Heavy Duty Chucks, Drawbar Operated	48
3-7	Metric Tongue and Groove Chucks, Master Jaw	50
3-8	Square Serrated, Heavy Duty Chucks, Wrench or Drawbar Operated	51
3-9	Square Serrated, Heavy Duty Chucks, Top-Jaw Master Key	52
3-10	Square Serrated, Heavy Duty Chucks, Master Jaw Nut	53
3-11	Square Serrated, Heavy Duty Chucks, Three-Step Reversible Top Jaw	54
3-12	Acme Serrated, Heavy Duty Chucks, Power Wrench or Drawbar Operated	55
3-13	Acme Serrated, Master Key	56
3-14	Acme Serrated, Jaw Nut	57
3-15	Acme Serrated, Three-Step Reversible Top Jaw	58
3-16	90 deg Serrated Jaw Interface (Inch), Serration Data	59
3-17	90 deg Serrated Jaw Interface (Inch), Accumulated Pitch Variation	60
3-18	60 deg Serrated Jaw Interface (Metric), Serration Data	61
3-19	60 deg Serrated Jaw Interface (Metric), Accumulated Pitch Variation	62
3-20	60 deg Metric and 90 deg Inch Serrated Jaws and Jaw-Nut Interface	63
3-21	1.5 mm × 60 deg Serrated Top Jaw (Metric)	64
3-22	Pin Locator Chucks, Master Jaw	65
3-23	Ball Style Chucks, Master Jaw	66
3-24	Ball Style Chucks, Top Jaw	67
3-25	Ball Style Chucks, Jaw Nut	68

Mandatory Appendix

I	Calculation of Force, Torque, and Speed	79
---	---	----

Nonmandatory Appendix

A	Legacy Data	83
---	-------------------	----