Standard for Elevator Suspension, Compensation, and Governor Systems

AN AMERICAN NATIONAL STANDARD



Standard for Elevator Suspension, Compensation, and Governor Systems

AN AMERICAN NATIONAL STANDARD



Date of Issuance: July 30, 2010

The next edition of this Standard is scheduled for publication in 2013. There will be no addenda issued to this edition.

ASME issues written replies to inquiries concerning interpretations of technical aspects of this Standard. The interpretations will be included with each edition. Interpretations are published on the ASME Web site under the Committee Pages at http://cstools.asme.org as they are issued.

ASME is the registered trademark of The American Society of Mechanical Engineers.

This code or standard was developed under procedures accredited as meeting the criteria for American National Standards. The Standards Committee that approved the code or standard was balanced to assure that individuals from competent and concerned interests have had an opportunity to participate. The proposed code or standard was made available for public review and comment that provides an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not "approve," "rate," or "endorse" any item, construction, proprietary device, or activity.

ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable letters patent, nor assumes any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representative(s) or person(s) affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations of this document issued in accordance with the established ASME procedures and policies, which precludes the issuance of interpretations by individuals.

No part of this document may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

The American Society of Mechanical Engineers Three Park Avenue, New York, NY 10016-5990

Copyright © 2010 by THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS All rights reserved Printed in U.S.A.

CONTENTS

Foreword		v
	ster	vi
	re With ASME A17 Committee	xi
•		xii
Part 1	Stranded Carbon Steel Wire Ropes for Elevators	1
Section 1.1	Scope	1
Section 1.2	References	1
Section 1.3	Terminology	2
Section 1.4	Material	7
Section 1.5	Rope Workmanship and Finish	8
Section 1.6	Properties and Tolerances of Newly Constructed Rope	9
Section 1.7	Testing And Compliance for Newly Constructed Rope	11
Section 1.8	Ordering Information	12
Section 1.9	Packaging and Identification	13
Section 1.10	Replacement Criteria	13
	•	
Mandatory App		1.77
I	Tables	17
Part 2	Aramid Fiber Ropes for Elevators	25
Section 2.1	Scope	25
Section 2.2	References	25
Section 2.3	Terminology	25
Section 2.4	Material	27
Section 2.5	Properties and Tolerances of Newly Constructed Rope	27
Section 2.6	Newly Constructed Rope Dimensions for Circular Cross-Section Designs (Type I)	28
Section 2.7	Newly Constructed Rope Dimensions for Noncircular Cross- Section Designs (Type II)	28
Section 2.8	Testing and Compliance	28
Section 2.9	Replacement Criteria	29
Part 3	Noncircular Elastomeric Coated Steel Suspension Members for	
	Elevators	30
Section 3.1	Scope	30
Section 3.2	References	30
Section 3.3	Terminology	30
Section 3.4	Material	31
Section 3.5	Properties and Tolerances	31
Section 3.6	Testing and Compliance	32
Section 3.7	Replacement Criteria	32
Figures		
1.3.1.1-1	Elements of Stranded Steel Wire Rope	2
1.3.1.3.2-1	Round Strand	3
1.3.1.3.2-2	Compacted Round Strand: Before and After Compacting	3
1.3.1.3.3-1	Lay Direction of Strands for Stranded Ropes	3
1.3.1.3.4-1	Seale Construction (e.g., 19S, 9-9-1)	3
1.3.1.3.4-2	Warrington Construction [e.g., 19W, (6+6)-6-1]	3
1.3.1.3.4-3	Filler Construction (e.g., 25F, 12-6F-6-1)	3
1.3.1.4-1	Examples of Cores	4

1.3.2.4.2-1	Regular (Ordinary) Lay and Lang Lay	5
1.3.3.1.1-1	Diameter of Round Rope	5
1.3.3.2.1-1	Strand Lay Length	5
1.3.3.2.2-1	Rope Lay Length	6
Tables		
1.4.1-1	Wire Level or Tensile Strength Grades for Given Rope Grades	7
1.4.1.1-1	Wire Level or Tensile Strength Grade Requirements	8
1.4.1.1-2	Wire Torsion Requirements	8
1.6.4.1-1	Weight of Coating for Final-Galvanized or Final-Coated	
	Zn-5Al-MM Rope Wire for Newly Constructed Rope	10
1.6.4.1-2	Weight of Coating for Drawn-Galvanized or Drawn-Coated	
	Zn-5Al-MM Rope Wire for Newly Constructed Rope	10
1.6.6.1.1-1	Tolerances on Rope Diameter (Stranded Rope) for Newly	
	Constructed Rope With Cores of Fiber or Other Nonmetallic	
	Materials	10
1.6.6.1.1-2	Tolerances on Rope Diameter (Stranded Rope) for Newly	
	Constructed Rope With Steel or Steel-Based Composite Cores	11
1.6.6.1.2-1	Permissible Differences in Rope Diameter for Newly Constructed	
	Rope	11
1.8.1-1	Ordering Information	13
1.10.1.2-1	Wire Breaks: Crown Wire Breaks Per Lay Length	14
1.10.3-1	Minimum Diameter	15
2.4.1.1-1	Nominal Aramid Yarn Property Values	27
2.4.1.1-2	Aramid Resin Impregnated Strand Property Values	27
2.6.2-1	Tolerances on Diameter	28
2.7.2-1	Tolerances on Dimensions	29
3.5.7-1	Tolerances on Nominal Noncircular Elastomeric Coated Steel	
	Suspension Member Sizes	32
Nonmandatory		
A	Inspection and Replacement of Steel Wire Ropes	35