FORM CRPV-2A RECOMMENDED FORM FOR QUALIFYING THE LAMINATE DESIGN Page of AND THE LAMINATE PROCEDURE SPECIFICATION USED IN MANUFACTURING COMPOSITE REINFORCED PRESSURE VESSELS

As required by the Provisions of the ASME Boiler and Pressure Vessel Code, Section VIII, Division 3

Qualification Test Report No.					
Laminate Procedure Specification No.					
A change in any of the essential	variables denoted by an aste	risk below requires a new Laminate Pro	ocedure Specification		
*Fiber		and Designation)			
*Sizing or Finish					
*Resin		acturer and Designation)			
*Curing Agent		rer, and Designation)			
Curing Agent/Resin Ratio	**	facturer, and Designation)			
Viscosity of Resin System	(min.) to	(max.) @			
*Manner of Impregnation					
*Percent Fiber by Weight in Composite	(Prepreg., Wet Wind, Postpreg.)				
*Variables of Winding Process [See Note (2)]		[See Note (1)]			
Helix Angle		(measured on cyli	inder between axis and band path)		
Circumferential Band Density		end/unit length.			
Circumferential Band Width					
Tension: Per Strand (End), Roving, or Band (spec	cify which)	per			
Method of Control		Program			
Layer Sequence					
*Primer	[See Note (2)]				
Primer Application Method		rer, and Designation)			
*Primer Curing Schedule	for	hr	min		
Exterior Treatment (Non-Structural, Describe)					
Fiber Type	Fiber Form	Manufacturer	Manufacturing No.		
Material No. 1					
Material No. 2 ———————————————————————————————————					
*Inner Liner	[Material Grade	and Thickness. See Note (1)]			
*Liner Size and Configuration					
Laminate Strength	,	(Length) Method of Measurement	(Cylindrical, Spherical, Other)		
Interlaminar Shear Strength			(If other than ASTM D2290)		
Acoustic Emission Test Report Number					

NOTES:

- (1) Where a range of values or a tolerance applies, state the applicable range or tolerance.
- (2) Use O to indicate full layer of circumferential windings (down and back), include number of passes. Use o to indicate half layer of circumferential windings (single pass).

FORM CRPV-2A

Page of	Page	of
---------	------	----

*Laminate Curing Schedule	(temperature)	for	hr	min
		for	hr	min
	(temperature)	for	hr	min
	(temperature)	for	hr	min
	(temperature)	for	hr	min
Manner of Measuring Temp	(temperature) perature: Oven Air		Wrong Surface	
Vessel Head		Other (C	Describe)	
*Barcol Hardness				
Laminate Thickness	(Use	a separate sheet to record in	ndividual readings and their location [See Note	(1)])
*Volumetric Expansion	(U		d individual readings and their location [See Not	:e (1)])
Gel Time				ire
			@	maximum test temperature
Maximum Temp. Cycle Test: _	(no. of cycles)			
Burst Pressure	(no. of cycles)			
			Pressure	
Oualification:	suits			
	ation Number			
ASME BOILER AND PRESSUR	·			
			(Year)	1
We certify that the statements i	n this Specification are co	rrect:		
Date		Signed		
		Ву		
Certificate of Authorization Nu	mber (U3)		Expires	
Certificate of Authorization Nur	mber (RP)		Expires	
		EDTIFICATION DV CIL	OR INCREATOR	
OF		ERTIFICATION BY SHO IINATE DESIGN AND	LAMINATE PROCEDURE SPECIFICA	TION
Laminate Procedure Specific	ation of		at	
			process of mai	
= :				
			Board of Boiler and Pressure Ves	
			of	
			e Qualification Test Report of the	=
			he Manufacturer has constructed	
			I the Laminate Design and Procedur warranty, expressed or implied, co	
			ctor nor his employer shall be liabl	
injury or property damage or			vith this inspection.	
Date	Signed(Author	orized Inspector)	Commissions(National Board	Authorized Inspector Commission number)