

ASME A17.6-2017
(Revision of ASME A17.6-2010)

Standard for Elevator Suspension, Compensation, and Governor Systems

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**

ASME A17.6-2017
(Revision of ASME A17.6-2010)

Standard for Elevator Suspension, Compensation, and Governor Systems

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**

Two Park Avenue • New York, NY • 10016 USA

Date of Issuance: August 6, 2018

The next edition of this Standard is scheduled for publication in 2022.

ASME issues written replies to inquiries concerning interpretations of technical aspects of this Standard. Interpretations are published on the ASME website under the Committee Pages at <http://cstools.asme.org/> as they are issued.

Errata to codes and standards may be posted on the ASME website under the Committee Pages to provide corrections to incorrectly published items, or to correct typographical or grammatical errors in codes and standards. Such errata shall be used on the date posted.

The Committee Pages can be found at <http://cstools.asme.org/>. There is an option available to automatically receive an e-mail notification when errata are posted to a particular code or standard. This option can be found on the appropriate Committee Page after selecting “Errata” in the “Publication Information” section.

ASME is the registered trademark of The American Society of Mechanical Engineers.

This code or standard was developed under procedures accredited as meeting the criteria for American National Standards. The Standards Committee that approved the code or standard was balanced to assure that individuals from competent and concerned interests have had an opportunity to participate. The proposed code or standard was made available for public review and comment that provides an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not “approve,” “rate,” or “endorse” any item, construction, proprietary device, or activity.

ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable letters patent, nor assume any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representative(s) or person(s) affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations of this document issued in accordance with the established ASME procedures and policies, which precludes the issuance of interpretations by individuals.

No part of this document may be reproduced in any form,
in an electronic retrieval system or otherwise,
without the prior written permission of the publisher.

The American Society of Mechanical Engineers
Two Park Avenue, New York, NY 10016-5990

Copyright © 2018 by
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS
All rights reserved
Printed in U.S.A.

CONTENTS

Foreword	v
Committee Roster	vi
Preface	xv
Summary of Changes	xvii
Part 1	
Stranded Carbon Steel Wire Ropes for Elevators	1
Section 1.1 Scope	1
Section 1.2 References	1
Section 1.3 Terminology	2
Section 1.4 Material	7
Section 1.5 Rope Workmanship and Finish	8
Section 1.6 Properties and Tolerances of Newly Constructed Rope	8
Section 1.7 Testing and Compliance for Newly Constructed Rope	10
Section 1.8 Ordering Information	12
Section 1.9 Packaging and Identification	12
Section 1.10 Replacement Criteria	12
Part 2	
Aramid Fiber Ropes for Elevators	16
Section 2.1 Scope	16
Section 2.2 References	16
Section 2.3 Terminology	16
Section 2.4 Material	18
Section 2.5 Properties and Tolerances of Newly Constructed Rope	18
Section 2.6 Newly Constructed Rope Dimensions for Circular Cross-Section Designs (Type I)	19
Section 2.7 Newly Constructed Rope Dimensions for Noncircular Cross-Section Designs (Type II)	19
Section 2.8 Testing and Compliance	19
Section 2.9 Replacement Criteria	20
Part 3	
Noncircular Elastomeric-Coated Steel Suspension Members for Elevators	22
Section 3.1 Scope	22
Section 3.2 References	22
Section 3.3 Terminology	22
Section 3.4 Material	23
Section 3.5 Properties and Tolerances	23
Section 3.6 Testing and Compliance	24
Section 3.7 Replacement Criteria	24
Mandatory Appendix	
I Rope Classifications Used in Part 1	26

Nonmandatory Appendix

A	Inspection and Replacement of Steel Wire Ropes	34
---	--	----

Figures

1.3.1.1-1	Elements of Stranded Steel Wire Rope	2
1.3.1.3.2-1	Round Strand	3
1.3.1.3.2-2	Compacted Round Strand: Before and After Compacting	3
1.3.1.3.3-1	Lay Direction of Strands for Stranded Ropes	3
1.3.1.3.4-1	Seale Construction (e.g., 19S, 9-9-1)	3
1.3.1.3.4-2	Warrington Construction [e.g., 19W, (6+6)-6-1]	3
1.3.1.3.4-3	Filler Construction (e.g., 25F, 12-6F-6-1)	3
1.3.1.4-1	Examples of Cores	4
1.3.2.4.2-1	Regular (Ordinary) Lay and Lang Lay	5
1.3.3.1.1-1	Diameter of Round Rope	5
1.3.3.2.1-1	Strand Lay Length	5
1.3.3.2.2-1	Rope Lay Length	6
A-1	Inspection and Replacement of Steel Wire Rope(s)	35

Tables

1.4.1-1	Wire Level or Tensile Strength Grades for Given Rope Grades	7
1.4.1.1-1	Wire Level or Tensile Strength Grade Requirements	8
1.4.1.1-2	Wire Torsion Requirements	8
1.6.4.1-1	Weight of Coating for Final-Galvanized or Final-Coated Zn-5Al-MM Rope Wire for Newly Constructed Rope	10
1.6.4.1-2	Weight of Coating for Drawn-Galvanized or Drawn-Coated Zn-5Al-MM Rope Wire for Newly Constructed Rope	10
1.6.6.1.1-1	Tolerances on Rope Diameter (Stranded Rope) for Newly Constructed Rope With Cores of Fiber or Other Nonmetallic Materials	10
1.6.6.1.1-2	Tolerances on Rope Diameter (Stranded Rope) for Newly Constructed Rope With Steel or Steel-Based Composite Cores	11
1.6.6.1.2-1	Permissible Differences in Rope Diameter for Newly Constructed Rope	11
1.8.1-1	Ordering Information	13
1.10.1.2-1	Wire Breaks: Crown Wire Breaks Per Lay Length	14
1.10.3-1	Minimum Diameter	15
2.4.1.1-1	Nominal Aramid Yarn Property Values	18
2.4.1.1-2	Aramid Resin Impregnated Strand Property Values	18
2.6.2-1	Tolerances on Diameter	19
2.7.2-1	Tolerances on Dimensions	20
3.5.7-1	Tolerances on Nominal Noncircular Elastomeric-Coated Steel Suspension Members Sizes	24
I-1.1-1	Classification 6 × 19 FC, Round Strand, Fiber Core or Polymer Core	27
I-1.1-2	Classification 8 × 19 FC, Round Strand, Fiber Core or Polymer Core	29
I-1.1-3	Classification 8 × 19, Round Strand, Steel Core	31
I-1.1-4	Classification 6 × 19, Round Strand, Steel Cores	33