

ASME B18.24-2023
(Revision of ASME B18.24-2020)

Part Identifying Number (PIN) Code System Standard for B18 Fastener Products

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**

ASME B18.24-2023
(Revision of ASME B18.24-2020)

Part Identifying Number (PIN) Code System Standard for B18 Fastener Products

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**

Two Park Avenue • New York, NY • 10016 USA

Date of Issuance: October 16, 2023

This Standard will be revised when the Society approves the issuance of a new edition.

This code or standard was developed under procedures accredited as meeting the criteria for American National Standards. The standards committee that approved the code or standard was balanced to ensure that individuals from competent and concerned interests had an opportunity to participate. The proposed code or standard was made available for public review and comment, which provided an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not “approve,” “certify,” “rate,” or “endorse” any item, construction, proprietary device, or activity. ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable letters patent, nor does ASME assume any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representatives or persons affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations of this document issued in accordance with the established ASME procedures and policies, which precludes the issuance of interpretations by individuals.

The endnotes and preamble in this document (if any) are part of this American National Standard.



ASME Collective Membership Mark

“ASME” and the above ASME symbol are registered trademarks of The American Society of Mechanical Engineers.

No part of this document may be reproduced in any form,
in an electronic retrieval system or otherwise,
without the prior written permission of the publisher.

The American Society of Mechanical Engineers
Two Park Avenue, New York, NY 10016-5990

Copyright © 2023 by
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS
All rights reserved

CONTENTS

Foreword		ix
Committee Roster		x
Correspondence With the B18 Committee		xi
Summary of Changes		xiii
1	Introductory Notes	1
2	General Guidance	1
3	PIN Code Structure	2
 Nonmandatory Appendices		
A	ASME B18.24.1, ASME B18.24.2, and ASME B18.24.3 Pin Succession Instructions	109
B	ASME B18.24.1, ASME B18.24.2, and ASME B18.24.3 Pin Succession Tables	115
C	Part Identifying Number System for Bent Bolts Per ASME B18.31.5	201
 Figure		
C-1	Part Identification Number (PIN) System for Bent Bolts	202
 Tables		
Sample 1-1	Fastener Family and Type/Base PIN	3
1-1	Fastener Family and Type/Base PIN	5
2-1	Thread Type	33
2-2	Thread and Point Options for Tapping Screws	33
3-1	Inch Thread	34
3-2	Inch Size	35
3-3	Metric Thread	36
3-4	Metric Size	37
3-5	Miniature Screw Thread	38
3-6	Inch Tapping Screw Thread	39
3-7	Metric Tapping Screw Thread	40
3-8	Inch Hex Socket Head Shoulder Screw Size	40
3-9	Metric Hex Socket Head Shoulder Screw Size	40
3-10	Inch Spline Socket Set Screw Thread	40
3-11	Inch Trim Head Machine Screw Size	40
3-12	Inch Wood Screw Thread	41
3-13	Inch Lag Screw Thread	41
3-14	Inch Rivet Size Weight	41
3-15	Inch Rivet Size Number	41
3-16	Inch Rivet Size 1	42
3-17	Inch Rivet Size/Length	42

3-18	Inch Pin Size 1	42
3-19	Inch Pin Size 2	43
3-20	Retaining Ring Size Number	44
3-21	Inch Retaining Ring Size	46
3-22	Inch Washer Size 1	47
3-23	Inch Washer Size 2	47
3-24	Inch Washer Size 3	48
3-25	Inch Washer Size 4	48
3-26	Metric Washer Size 1	49
3-27	Metric Washer Size 2	49
3-28	Metric Key Size 1	50
3-29	Metric Key Size 2	50
4-1	Inch Length/Other	51
4-2	Metric Length/Other	53
4-3	Inch Miniature Screw Length	54
4-4	Insert Length	54
4-5	Inch PIN Length	54
4-6	Inch Eyebolt Full Thread Length	55
5-1	Material and Treatment: ASTM Material Specifications	56
5-2	Material and Treatment: UNS Carbon and Alloy Steels	81
5-3	Material and Treatment: UNS Heat and Corrosion Resisting Steels	86
5-4	Material and Treatment: UNS Nonferrous Materials	90
5-5	Material and Treatment: SAE Material Specifications	92
5-6	Material and Treatment: ISO Material Specifications	92
5-7	Material and Treatment: IFI Material Specifications	93
5-8	Material and Treatment: ASME B18.16.1M	93
5-9	Material and Treatment: ASME B18.6.6	93
5-10	Material and Treatment: ASME B18.6.3	93
5-11	Material and Treatment: ASME B18.16.4	93
6-1	Plating, Coating, and Passivation: Plain, Unfinished	93
6-2	Plating, Coating, and Passivation: ASTM Finish Specifications	94
6-3	Plating, Coating, and Passivation: Government Finish Specifications	106
6-4	Plating, Coating, and Passivation: SAE Finish Specifications	106
6-5	Plating, Coating, and Passivation: ISO Finish Specifications	107
7-1	Plain: No Additional Features	107
7-2	Miscellaneous Features for Externally Threaded Fasteners	107
7-3	General Point Options	107
7-4	Features for Metric Flange Screws	107
7-5	Features for Metric 12-Spline Screws	107
7-6	Neck Options for Large Rivets	107
7-7	Cotter PIN Type	107
7-8	PIN Type	107
7-9	SEMs Washer Components	108
7-10	Wood Screw Thread Types	108
7-11	Miscellaneous Features for Socket Head Cap Screws	108

7-12	Self-Locking Elements for Set Screws	108
7-13	Thread Class for Track Bolts and Nuts	108
7-14	Alternate Points for Thumb and Wing Screws (ASME B18.6.8)	108
B-1	Fastener Family	115
B-2	Fastener Type: Externally Threaded	116
B-3	Fastener Type: Internally Threaded and Nonthreaded	133
B-4	Thread Series: Externally Threaded	136
B-5	Thread Series: Internally Threaded	136
B-6	Inch Size: Externally Threaded	137
B-7	Inch Size: Internally Threaded	137
B-8	Metric Size: Externally Threaded	138
B-9	Metric Size: Internally Threaded	138
B-10	Inch Miniature Screw Size	139
B-11	Inch Length: Externally Threaded	139
B-12	Metric Length: Externally Threaded	140
B-13	Inch Miniature Screw Length	140
B-14	Length: Internally Threaded	140
B-15	Dimensions/Other Characteristics: Nonthreaded	140
B-16	Dimensions/Other Characteristics: Nonthreaded	140
B-17	Dimensions/Other Characteristics: Nonthreaded	141
B-18	Dimensions/Other Characteristics: Nonthreaded	141
B-19	Dimensions/Other Characteristics: Nonthreaded	141
B-20	Dimensions/Other Characteristics: Nonthreaded	142
B-21	Dimensions/Other Characteristics: Nonthreaded	142
B-22	Dimensions/Other Characteristics: Nonthreaded	142
B-23	Dimensions/Other Characteristics: Nonthreaded	142
B-24	Dimensions/Other Characteristics: Nonthreaded	143
B-25	Dimensions/Other Characteristics: Nonthreaded	143
B-26	Dimensions/Other Characteristics: Nonthreaded	143
B-27	Dimensions/Other Characteristics: Nonthreaded	144
B-28	Dimensions/Other Characteristics: Nonthreaded	144
B-29	Dimensions/Other Characteristics: Nonthreaded	145
B-30	Dimensions/Other Characteristics: Nonthreaded	145
B-31	Dimensions/Other Characteristics: Nonthreaded	146
B-32	Dimensions/Other Characteristics: Nonthreaded	146
B-33	Dimensions/Other Characteristics: Nonthreaded	147
B-34	Dimensions/Other Characteristics: Nonthreaded	147
B-35	Dimensions/Other Characteristics: Nonthreaded	148
B-36	Dimensions/Other Characteristics: Nonthreaded	148
B-37	Dimensions/Other Characteristics: Nonthreaded	149
B-38	Dimensions/Other Characteristics: Nonthreaded	149
B-39	Dimensions/Other Characteristics: Nonthreaded	150
B-40	Dimensions/Other Characteristics: Nonthreaded	150
B-41	Dimensions/Other Characteristics: Nonthreaded	151
B-42	Dimensions/Other Characteristics: Nonthreaded	151

B-133	Dimensions/Other Characteristics: Nonthreaded	182
B-134	Material and Treatment A	183
B-135	Material and Treatment B	188
B-136	Plating, Coating, and Passivation	192
B-137	Additional Features: Externally Threaded	193
B-138	Additional Features: Internally Threaded	193
B-139	Additional Features: Nonthreaded	193
B-140	Cross Reference: Table 2-2 Tapping Screw Point AB	193
B-141	Cross Reference: Table 2-2 Tapping Screw Point B	193
B-142	Cross Reference: Table 2-2 Tapping Screw Point BF	193
B-143	Cross Reference: Table 2-2 Tapping Screw Point BP	193
B-144	Cross Reference: Table 2-2 Tapping Screw Point BT	193
B-145	Cross Reference: Table 2-2 Tapping Screw Point C	194
B-146	Cross Reference: Table 2-2 Tapping Screw Point D	194
B-147	Cross Reference: Table 2-2 Tapping Screw Point F	194
B-148	Cross Reference: Table 2-2 Tapping Screw Point G	194
B-149	Cross Reference: Table 2-2 Tapping Screw Point T	194
B-150	Cross Reference: Table 2-2 Tapping Screw Point U	194
B-151	Bridge to Table 3-6 for AB, B, BF, BP, BT	194
B-152	Bridge to Table 3-6 for C, D, F, G, T	194
B-153	Bridge to Table 3-7 for AB, B, BF, BT	194
B-154	Bridge to Table 3-7 for D, F, T	194
B-155	Bridge to Table 3-10	194
B-156	Bridge to Table 3-12	195
B-157	Bridge to Table 3-13	195
B-158	Cross Reference: Table 7-9 Washer Component 1	195
B-159	Cross Reference: Table 7-9 Washer Component 2	195
B-160	Cross Reference: Table 7-9 Washer Component 3	195
B-161	Cross Reference: Table 7-9 Washer Component 4	195
B-162	Cross Reference: Table 7-9 Washer Component 5	195
B-163	Cross Reference: Table 7-9 Washer Component 6	195
B-164	Cross Reference: Table 7-9 Washer Component 7	195
B-165	Cross Reference: Table 7-9 Washer Component 8	195
B-166	Cross Reference: Table 7-9 Washer Component 9	195
B-167	Cross Reference: Table 7-9 Washer Component 10	195
B-168	Cross Reference: Table 7-9 Washer Component 11	196
B-169	Cross Reference: Table 7-9 Washer Component 12	196
B-170	Bridge to Table 3-11	196
B-171	Bridge to Table 3-4	196
B-172	Bridge to Table 7-10	196
B-173	ASME B18.24 Legacy Table References From ASME B18.24.1, ASME B18.24.2, and ASME B18.24.3	197
C-1	Materials for Bent Bolts	203
C-2	Finish Designations for Bent Bolts	203