

ASME B89.4.10360.2-2008

**Acceptance Test and
Reverification Test for
Coordinate Measuring
Machines (CMMs) —
Part 2: CMMs Used for
Measuring Linear
Dimensions**

Contents	Page
Foreword	vii
Committee Roster	viii
Introduction.....	ix
1 Scope.....	1
2 Normative references.....	2
3 Terms and definitions	2
4 Symbols.....	6
5 Environmental and metrological requirements.....	7
5.1 Environmental conditions	7
5.2 Operating conditions	9
5.3 Length measurement error, E_L	9
5.4 Repeatability range of the length measurement error, R_0	9
5.5 Workpiece loading effects	10
6 Acceptance tests and reverification tests	10
6.1 General	10
6.2 Principle.....	12
6.3 Length measurement error with zero ram axis stylus tip offset, E_0	12
6.3.1 General	12
6.3.2 Measuring equipment	12
6.3.3 Procedure.....	13
6.3.4 Derivation of test results	15
6.4 Repeatability range of the length measurement error, R_0	16
6.5 Length measurement error with ram axis stylus tip offset of length 150 mm, E_{150}	16
6.5.1 Measuring equipment	16
6.5.2 Procedure.....	16
6.5.3 Derivation of test results	19
6.6 Dual ram CMMs.....	19
6.6.1 Simplex operating mode.....	19
6.6.2 Duplex operating mode.....	19
7 Compliance with specifications	20
7.1 Acceptance test.....	20
7.1.1 Acceptance criteria	20
7.1.2 Data rejection and repeated measurements.....	21
7.1.3 Thermal derating of specifications	23
7.2 Reverification test	27
8 Applications	27
8.1 Acceptance test.....	27
8.2 Reverification test	27
8.3 Interim check	28
9 Indication in product documentation and data sheets.....	28
Annex A (informative) Interim check.....	29
A.1 Interim check of the CMM	29

A.2	Interim testing and the comparison to specifications	29
A.2.1	General	29
A.2.2	Interim testing using uni-directional artefacts.....	30
Annex B	(normative) Artefacts that represent a calibrated test length	31
B.1	General	31
B.2	Bi-directional measurements.....	32
B.2.1	General	32
B.2.2	Gauge blocks.....	32
B.2.3	Step gauges measured in a bi-directional manner.....	32
B.2.4	Ball bars / ball plates measured in a bi-directional manner	32
B.2.5	Laser interferometry with contact probing measured in a bi-directional manner	32
B.3	Uni-directional measurements (must be supplemented with bi-directional measurements).....	33
B.3.1	General	33
B.3.2	Calibrated test length composed of uni-directional and short gauge block measurements.....	33
B.3.3	Artefacts for uni-directional measurements	34
Annex C	(informative) Alignment of gauges.....	36
C.1	General	36
C.2	Parallel face gauges.....	36
C.3	Ball bar/ball plate gauges.....	36
Annex D	(normative) Mathematical adjustments to Low CTE artefacts	38
D.1	General	38
D.2	Requirements	38
Annex E	(informative) Location of the single stylus probing test	
Annex F	(informative) Relation to the GPS matrix model	
F.1	Information about this part of ISO 10360 and its use	
F.2	Position in the GPS matrix model	
F.3	Related standards	

Note: Annexes E and F originally in the ISO Standard are omitted in the B89 Technical Report because they pertain only to the location of other ISO documents and are not relevant to this Report.

Annex E	(normative) Test uncertainty	40
Annex F	(normative) Traceability of calibrated test lengths	52
Annex G	(normative) Decision rule for conformance testing	54
Annex H	(informative) Interim testing of CMM systems	55
Annex I	(normative) ASME B89.4.10360.2 Data sheet	65
Annex J	(informative) Figures 12, 13 and 14 from ISO 10360-1:2000	66

Bibliography	67
---------------------------	-----------