

ASME B18.2.1-2012

(Revision of ASME B18.2.1-2010)

Square, Hex, Heavy Hex, and Askew Head Bolts and Hex, Heavy Hex, Hex Flange, Lobed Head, and Lag Screws (Inch Series)

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**

ASME B18.2.1-2012
(Revision of ASME B18.2.1-2010)

Square, Hex, Heavy Hex, and Askew Head Bolts and Hex, Heavy Hex, Hex Flange, Lobed Head, and Lag Screws (Inch Series)

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**

Two Park Avenue • New York, NY • 10016 USA

Date of Issuance: April 24, 2013

This Standard will be revised when the Society approves the issuance of a new edition.

ASME issues written replies to inquiries concerning interpretations of technical aspects of this Standard. Periodically certain actions of the ASME B18 Committee may be published as Cases. Cases and interpretations are published on the ASME Web site under the Committee Pages at <http://cstools.asme.org> as they are issued.

Errata to codes and standards may be posted on the ASME Web site under the Committee Pages to provide corrections to incorrectly published items, or to correct typographical or grammatical errors in codes and standards. Such errata shall be used on the date posted.

The Committee Pages can be found at <http://cstools.asme.org/>. There is an option available to automatically receive an e-mail notification when errata are posted to a particular code or standard. This option can be found on the appropriate Committee Page after selecting “Errata” in the “Publication Information” section.

ASME is the registered trademark of The American Society of Mechanical Engineers.

This code or standard was developed under procedures accredited as meeting the criteria for American National Standards. The Standards Committee that approved the code or standard was balanced to assure that individuals from competent and concerned interests have had an opportunity to participate. The proposed code or standard was made available for public review and comment that provides an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not “approve,” “rate,” or “endorse” any item, construction, proprietary device, or activity.

ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable letters patent, nor assumes any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representative(s) or person(s) affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations of this document issued in accordance with the established ASME procedures and policies, which precludes the issuance of interpretations by individuals.

No part of this document may be reproduced in any form,
in an electronic retrieval system or otherwise,
without the prior written permission of the publisher.

The American Society of Mechanical Engineers
Two Park Avenue, New York, NY 10016-5990

Copyright © 2013 by
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS
All rights reserved
Printed in U.S.A.

CONTENTS

Foreword	iv
Committee Roster	vii
Correspondence With the B18 Committee	viii
1 Introduction	1
2 General Data for Both Bolts and Screws	2
3 Bolts	4
4 Screws	9
5 Lag Screws	19
Figures	
1 Underhead Fillet for Long Screws	18
2 Underhead Fillet for Short Screws Threaded Full Length	18
3 L_G , Maximum and L_B , Minimum for Short Screws Threaded Full Length	19
Tables	
1 Dimensions of Square Head Bolts	5
2 Dimensions of Hex Bolts	6
3 Dimensions of Heavy Hex Bolts	7
4 Dimensions of Askew Head Bolts	8
5 Length Tolerances for Bolts	8
6 Dimensions of Hex Cap Screws	10
7 Dimensions of Heavy Hex Screws	12
8 Dimensions of Hex Flange Screws	14
9 Dimensions of Lobed Head Screws	16
10 Dimensions of Underhead Fillets	17
11 L_G , Maximum and L_B , Minimum Limitations for Short Screws Threaded Full Length	18
12 Maximum Grip Gaging Lengths, L_G , and Minimum Body Lengths, L_B , for Screws Except Flange Head	20
13 Length Tolerances for Screws	23
14 Dimensions of Square Lag Screws	24
15 Dimensions of Hex Lag Screws	25
16 Dimensions of Lag Screw Threads	25
Mandatory Appendix	
I Gage and Gaging Practices for External Lobed Head Drive System	27
Nonmandatory Appendices	
A Formulas for Bolt and Screw Head Dimensions	30
B Weight in Pounds of 100 Steel Hex Cap Screws for Given Diameter/Length Combination	32
C Countersunk Center Holes	33
D Self-Locking Element and Drilled Head Guidelines	34